

# CONIPAC 1000

## Specification packaging materials data sheet

### Technical Data

Nominal volume	ca. 1000 liter / approx. 264 gal.
Outer Diameter	ca. 1160 mm / approx. 45.7 in.
Total height	ca. 1330 mm / approx. 51.2 in.
Bottom outlet	2" ball valve
Weight	min. 65,0 kg / min. 143.3 lb.



### Construction and description

Container	<ul style="list-style-type: none"> <li>• Especially suitable for sensitive products in the pharmaceutical or food industries</li> <li>• manufactured by a coextrusion blow moulding process</li> <li>• Coex 2 Layer wall-design (HD PE)</li> </ul>
Design	<ul style="list-style-type: none"> <li>• designed to be handled by fork-lift or pallet jack</li> <li>• smooth interior walls for easy cleaning</li> <li>• when empty, 5 x nestable</li> <li>• 80% volume savings on return trip</li> <li>• ideal filling and draining</li> <li>• CONIPAC 1000 may not be pressurized</li> </ul>
Filling temperature	<ul style="list-style-type: none"> <li>• max. 60°C / max. 140°</li> </ul>
Density of filling medium	<ul style="list-style-type: none"> <li>• max. 1,4 kg/dm<sup>3</sup></li> </ul>

**Issued by/on**  
M. Monzel

**Revision status**  
29. Oct 2018/A