

## UC - Drum

1H1/Y1.9/300/.../D/BAM 6834-RIKUTEC / 16. Revision

### Specification packaging materials data sheet

#### Technical Data

Nominal volume	ca. 205 liter / approx. 54 gal.
Outer Diameter	ca. 581 mm / approx. 22.9 in.
Total height	ca. 955 mm / approx. 37.6 in.
Diameter filling opening	2 x S62 x 5mm
Weight	min. 14,0 kg / min. 30. 9 lb



#### Construction and description

Drum	<ul style="list-style-type: none"> <li>• manufactured by a coextrusion blow moulding process</li> <li>• Coex 2 Layer wall-design (HD PE)</li> <li>• Outer layer material : HD PE</li> <li>• Inner layer material : HD PE (virgin-no additives HD PE)</li> </ul>
Design	<ul style="list-style-type: none"> <li>• special designed double L-Ring on the top and bottom</li> <li>• 300 kPA pressure rated</li> </ul>
Bungs	<ul style="list-style-type: none"> <li>• 1 x S62 x 5 air vent cap of HD PE with PTFE laminate</li> <li>• 1 x S62 x 5 cap of HD PE</li> </ul>
Closing torques	requirement corresponding to dip tube and seal selection

**Issued by/on**  
M. Monzel

**Revision status**  
25. Oct 2018/A